

## Foot Operated Bottle Filling Fountain (Non-Chilled)



Product Code: DFWHCF-FOP

### Foot Operated Bottle Filling Fountain

Product Code DFWHCF-FOP

The foot operated bottle filling fountains are supplied with a WRAS approved foot valve and a handsfree bottle filling spout. Manufactured from stainless steel the units are robust and include a telescopic shroud to conceal the interconnecting pipework.

#### Dimensions & Specifications:

Width: 305mm.

Depth: 350mm from wall.

Height: 150mm plus 75mm rear upstand.

Telescopic shroud: 500mm to 950mm.

Material: 1.6mm thick - Stainless steel - grade 304.

To ensure the proper functioning and longevity of this unit, a Y-strainer or filter must be installed as part of the water supply system. The Y-strainer / filter is essential for protecting the internal components and maintaining the correct flow characteristics of the tap. Failure to install a Y-strainer or filter will result in the warranty being void.

#### Supplied With:

Bottle filling spout: swan neck no touch bottle filling spout.

Foot valve: WRAS approved foot operated valve.

Shroud: 500mm to 950mm telescopic pipework shroud.

Waste: 1.25" flush grated waste.

Pipework: Plastic WRAS approved pipework from valve to spout.

#### Delivery:

In stock usually delivered in one to two working days.

\*All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.

All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.\*\*