

**Drinking Fountain** 

Kestrel Court Harbour Road Portishead Bristol BS20 7AN

Phone: 01275 400456

Web: https://www.drinking-fountain.co.uk Email: sales@drinking-fountain.co.uk

# Foot Op Junior Height Bottle Filler & Drinking Fountain





Product Code: DFBF-FJ

#### Drinking Fountain And Bottle Filler Combined with Foot Operation. - Junior Height

Product Code DFBF-FJ

The drinking fountains with integral bottle filling units are designed to offer a vandal resistant dual purpose station where the user can either drink water, or fill their own water bottles. The integral bottle filler unit solves the two traditional problems associated with swan neck bottle fillers: users banging their heads on a swan neck filler fitted to a small fountain, and easily damage spouts, the unit is also hands free and supplied with foot buttons for both the bottle filler and drinking fountain.

A cover for the access hole can be added to make it free standing.

The drinking fountain with built in bottle filling station has a full height 900mm floor standing undershroud. The fountains are designed to be wall and floor mounted and provide drinking water with the option to fill reusable water bottles.

The drinking water is dispensed from a WRAS approved self closing bubbler tap mounted on the top right hand side of the unit, whilst bottle filling water is dispensed through the recess in the front of the shroud via a WRAS approved timed flow tap at the top of the bottle filling recess. The bottle filler recess is designed to take all common 0.5, 0.75. and 1 litre drinking water bottles.

The unit is constructed from 304 grade stainless steel, and is supplied with flexible waste pipework, and 15mm compression connections on the taps.

#### **Dimensions & Specifications:**

Width: 300mm wide. Depth: 300mm front to back. Height: 760mm high.

Material: Stainless steel - grade 304 - 1.2mm thick.

### **Recommended Mounting Heights For Drinking Water Fountains:**

Adult: 900 to 915mm. Junior: 762mm. Infant: 690mm. Secondary: 860mm.

## Supplied With:

Wall and floor fixing holes.
Waste fittings with flexible pipework and connecting T piece.
WRAS approved taps.
15mm compression fittings on the foot valves.

Delivery:

In stock, usually delivered in 1 to 2 working days.

\*\*All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.

All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.\*\*