

Drinking Fountain

Kestrel Court Harbour Road Portishead Bristol BS20 7AN

Phone: 01275 400456

Web: https://www.drinking-fountain.co.uk Email: sales@drinking-fountain.co.uk

Drinking Fountain With Shroud And WRAS Approved Tap



Product Code: DFWHS-WRAS

WRAS Compliant Shrouded Drinking Water Fountains

Product Code DFWHS-WRAS

The stainless steel shrouded drinking fountains are supplied complete with a WRAS approved drinking water bubbler. The tap has been tested and approved by the Water Research Advisory Scheme (WRAS), this ensures the tap complies with the Water Supply (Water Fittings) Regulations and Scottish Byelaws.

The WRAS approved bubbler tap is located to ensure ease of access by the user, and has a timed flow valve which automatically turns off after use to prevent water waste.

The shrouded drinking water fountains are manufactured from grade 304 stainless steel with a thickness of 1.6mm to ensure they are very robust and vandal resistant, the half height shroud conceals the pipework and has a removable access panel underneath.

Rounded front safety edges help to prevent accidental injury, whilst the smooth finish aids cleaning and hygiene. The small design footprint aids location choice and makes installation easier.

To ensure the proper functioning and longevity of this unit, a Y-strainer must be installed as part of the water supply system. The Y-strainer is essential for protecting the internal components and maintaining the correct flow characteristics of the tap. Failure to install a Y-strainer will result in the warranty being void.

Dimensions & Specifications:

Width: 305mm.

Depth: 350mm from wall.

Height: 245mm high plus 75mm rear upstand.

Material: 1.6mm thick - Stainless steel - grade 304.

Bubbler tap: WRAS approved bubbler tap.

Recommended Mounting Heights For Drinking Fountains:

Adult: 900 to 915mm. Junior: 762mm. Infant: 690mm. Secondary: 860mm.

Supplied With:

Integral wall fixing brackets.
32mm flush grated waste fitting.

WRAS approved chrome plated bubbler tap with shielded nozzle, self closing valve, and 15mm water pipe compression coupler.

Delivery:

In stock, usually delivered in one to two working days.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.

All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**