Drinking Fountain
5 Brearley Court, Baird Road Waterwells Business Park Gloucester GL2 2AF
Phone: 01275 400456
Web: https://www.drinking-fountain.co.uk
Email: sales@drinking-fountain.co.uk

316 Grade Wall Mounted Bottle Filler (Non-Chilled)



Product Code: 316-WMBF

316 Grade Stainless Steel Surface Mounted Bottle Filler

Product Code: 316-WMBF

This surface-mounted bottle filler is constructed from 316-grade stainless steel, offering superior corrosion resistance and durability, especially in harsh environments such as coastal or high-humidity areas. The versatile wall-mounted design allows for flexible installation at varying heights to accommodate users of different ages, making it ideal for schools, public buildings, or outdoor locations.

The WRAS-approved press button valve is simple to operate and features an on/off mechanism that automatically shuts off when released, helping to conserve water and reduce waste.

With rounded corners for added safety and a compact projection, this unit is perfect for high-traffic areas such as corridors where space is limited.

Key Features:

- Constructed from 316-grade stainless steel, providing excellent corrosion resistance and strength, particularly in environments exposed to saltwater or moisture.
- Press button on/off valve: WRAS approved for quality assurance, easy to use, and designed to turn off immediately when released, conserving water.
- **This unit does not have a built-in chilling system and will dispense water at the incoming mains water temperature, remote chillers are available.**
- Rounded corners help minimize the risk of injury, promoting safety in high-use areas.
- Compact 85mm projection: Ideal for installation in tight spaces like corridors or narrow passageways.
- Supplied with keyhole fixing holes, a 32mm waste fitting, and a flexible waste pipe for easy and efficient installation.
- To ensure the proper functioning and longevity of this unit, a Y-strainer or filter must be installed as part of the water supply system. The Y-strainer / filter is essential for protecting the internal components and maintaining the correct flow characteristics of the tap. Failure to install a Y-strainer or filter will result in the warranty being void.

Dimensions & Specifications:

Width: 350mm
Depth: 85mm (from the wall)
Height: 545mm

Bottle Aperture:

Height: 335mm
Width: 125mm

Material: 1.2mm thick 316-grade stainless steel for superior durability and corrosion resistance.

Bottle Filling Tap: WRAS-approved press button, time-flow mechanism for reliable and water-efficient bottle filling.

Supplied With:

Integral wall fixing points for easy installation.
32mm flush-grated waste fitting and flexible waste pipe.
Chrome-plated WRAS approved press button on/off bottle filling tap.

Delivery Information:

Usually dispatched from stock within 1 to 2 working days.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**